

Datum: 22.05.2012

Date:
Date:



Bemerkung Konfiguration (RZ)	Gegengewicht		Superlift			HA- -Pos.	SP- Länge [m]	SP- Offset	Deutsch			
	GG [t]	ZB [t]	MR / GGR [m] / [m]	SL-GG [t]	SL-Typ				Tabellen- Nummer	Index	Seiten	
SSL+LF2	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	253 717 12			
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	253 718 12		1-27	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	253 721 12		1-27	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	253 722 12		1-27	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	253 725 12		1-27	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	253 726 12		1-27	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	253 729 12		1-27	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	253 730 12		1-27	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	253 733 12		1-27	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	253 734 12		1-27	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	253 737 12		1-27	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	253 738 12		1-27	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	24 - 36	30°	254 910 12		1-18	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	24 - 36	30°	254 911 12		1-18	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	24 - 36	30°	254 914 12		1-18	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	24 - 36	30°	254 915 12		1-18	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	24 - 36	30°	254 918 12		1-18	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	24 - 36	30°	254 919 12		1-18	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	24 - 36	30°	254 922 12		1-18	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	24 - 36	30°	254 923 12		1-18	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	24 - 36	30°	254 926 12		1-18	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	24 - 36	30°	254 927 12		1-18	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	24 - 36	30°	254 930 12		1-18	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	24 - 36	30°	254 931 12		1-18	
	SSL/LSL+LF2	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	253 741 12		1-27
		160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	253 742 12		1-27
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	253 745 12		1-27
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	253 746 12		1-27
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	253 749 12		1-27
		160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	253 750 12		1-27
		180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	253 753 12		1-27
		160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	253 754 12		1-27
		180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	253 757 12		1-27
		160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	253 758 12		1-27
		180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	253 761 12		1-27
		160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	253 762 12		1-27
		180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	253 765 12		1-9
		160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	253 766 12		1-9
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	253 769 12		1-9
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	253 770 12		1-9
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	253 773 12		1-9
		160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	253 774 12		1-9
		180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	253 777 12		1-9
		160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	253 778 12		1-9
180 t		60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	253 781 12		1-9	
160 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	253 782 12		1-9	
180 t		60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	253 785 12		1-9	
160 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	253 786 12		1-9	
180 t		60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	253 789 12		1-27	
160 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	253 790 12		1-27	
180 t		60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	253 793 12		1-27	
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	253 794 12		1-27	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	253 797 12		1-27	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	253 798 12		1-27	
180 t		60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	253 801 12		1-27	
160 t		0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	253 802 12		1-27	
180 t		60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	253 805 12		1-27	
160 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	253 806 12		1-27	
180 t		60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	253 809 12		1-27	
160 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	253 810 12		1-27	

Datum: 22.05.2012

Date:
Date:



Bemerkung Konfiguration (RZ)	Gegengewicht		Superlift			HA- -Pos.	SP- Länge [m]	SP- Offset	Deutsch			
	GG [t]	ZB [t]	MR / GGR [m] / [m]	SL-GG [t]	SL-Typ				Tabellen- Nummer	Index	Seiten	
SSL/LSL+LF2	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	24 - 36	30°	254 934 12		1-18	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	24 - 36	30°	254 935 12		1-18	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	24 - 36	30°	254 938 12		1-18	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	24 - 36	30°	254 939 12		1-18	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	24 - 36	30°	254 942 12		1-18	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	24 - 36	30°	254 943 12		1-18	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	24 - 36	30°	254 946 12		1-18	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	24 - 36	30°	254 947 12		1-18	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	24 - 36	30°	254 950 12		1-18	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	24 - 36	30°	254 951 12		1-18	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	24 - 36	30°	254 954 12		1-18	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	24 - 36	30°	254 955 12		1-18	
	SH(+LF2)	alle		-	-	-	-	12 - 36	10°	254 590 12		1-30
		alle		-	-	-	-	12 - 36	15°	254 591 12		1-10
		alle		-	-	-	-	12 - 36	20°	254 592 12		1-30
	SH/LH(+LF2)	alle		-	-	-	-	12 - 36	10°	254 593 12		1-18
alle			-	-	-	-	12 - 36	15°	254 594 12		1-6	
alle			-	-	-	-	12 - 36	20°	254 595 12		1-18	
SSL(+LF2)	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	254 596 12		1-27	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	254 597 12		1-27	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	254 600 12		1-27	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	254 601 12		1-27	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	254 604 12		1-27	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	254 605 12		1-27	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	254 608 12		1-27	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	254 609 12		1-27	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	254 612 12		1-27	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	254 613 12		1-27	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	254 616 12		1-27	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	254 617 12		1-27	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	254 620 12		1-9	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	254 621 12		1-9	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	254 624 12		1-9	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	254 625 12		1-9	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	254 628 12		1-9	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	254 629 12		1-9	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	254 632 12		1-9	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	254 633 12		1-9	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	254 636 12		1-9	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	254 637 12		1-9	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	254 640 12		1-9	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	254 641 12		1-9	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	254 644 12		1-27	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	254 645 12		1-27	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	254 648 12		1-27	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	254 649 12		1-27	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	254 652 12		1-27	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	254 653 12		1-27	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	254 656 12		1-27	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	254 657 12		1-27	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	254 660 12		1-27	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	254 661 12		1-27	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	254 664 12		1-27	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	254 665 12		1-27	
	SSL/LSL(+LF2)	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	254 668 12		1-21
		160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	254 669 12		1-21
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	254 672 12		1-21
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	254 673 12		1-21
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	254 676 12		1-21
		160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	254 677 12		1-21
		180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	254 680 12		1-21
		160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	254 681 12		1-21
		180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	254 684 12		1-21
		160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	254 685 12		1-21
		180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	254 688 12		1-21
		160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	254 689 12		1-21



Bemerkung Konfiguration (RZ)	Gegengewicht		Superlift			HA-	SP-	SP-	Deutsch			
	GG [t]	ZB [t]	MR / GGR [m] / [m]	SL-GG [t]	SL-Typ	-Pos.	Länge [m]	Offset	Tabellen- Nummer	Index	Seiten	
SSL/LSL(+LF2)	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	254 692 12		1-7	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	254 693 12		1-7	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	254 696 12		1-7	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	254 697 12		1-7	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	254 700 12		1-7	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	254 701 12		1-7	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	254 704 12		1-7	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	254 705 12		1-7	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	254 708 12		1-7	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	254 709 12		1-7	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	254 712 12		1-7	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	254 713 12		1-7	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	254 716 12		1-21	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	254 717 12		1-21	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	254 720 12		1-21	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	254 721 12		1-21	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	254 724 12		1-21	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	254 725 12		1-21	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	254 728 12		1-21	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	254 729 12		1-21	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	254 732 12		1-21	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	254 733 12		1-21	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	254 736 12		1-21	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	254 737 12		1-21	
	SH/LH + SGL	160	0 t	-	-	-	-	-	-	167 475 12		1-1
		beide	60 t	-	-	-	-	-	-	167 476 12		1-2
	SSL/LSL + SGL	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	167 477 12		1-6
		180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	167 478 12		1-6
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	167 479 12		1-6
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	167 480 12		1-6
		160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	167 481 12		1-6
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	167 482 12		1-6
		160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	167 483 12		1-6
		180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	167 484 12		1-6
		160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	167 485 12		1-6
		180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	167 486 12		1-6
160 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	167 487 12		1-6	
180 t		60 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	167 488 12		1-6	
140 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	253 813 12		1-6	
120 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	253 814 12		1-6	
140 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	253 815 12		1-6	
120 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	253 816 12		1-6	
140 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	253 817 12		1-6	
120 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	253 818 12		1-6	
140 t		0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	253 819 12		1-6	
120 t		0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	253 820 12		1-6	
140 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	253 821 12		1-6	
120 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	253 822 12		1-6	
140 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	253 823 12		1-6	
120 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	253 824 12		1-6	
SH/LH + LF2 + SGL		alle		-	-	-	-	12 m	10°	253 837 12		1-7
		alle		-	-	-	-	12 m	15°	253 838 12		1-7
		alle		-	-	-	-	12 m	20°	253 839 12		1-7
SSL/LSL + LF2 + SGL		180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	253 840 12		1-6
		160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	253 841 12		1-6
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	253 844 12		1-6
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	253 845 12		1-6	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	253 848 12		1-6	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	253 849 12		1-6	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	10°	253 852 12		1-6	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	10°	253 853 12		1-6	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	10°	253 856 12		1-6	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	10°	253 857 12		1-6	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	10°	253 860 12		1-6	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	10°	253 861 12		1-6	

Datum: 22.05.2012

Date:
Date:




Bemerkung	Gegengewicht		Superlift			HA-Pos.	SP-Länge [m]	SP-Offset	Deutsch			
			MR / GGR [m] / [m]	SL-GG [t]	SL-Typ				Tabellen-Nummer	Index	Seiten	
												GG [t]
SSL/LSL + LF2 + SGL	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	253 864 12		1-6	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	253 865 12		1-6	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	253 868 12		1-6	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	253 869 12		1-6	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	253 872 12		1-6	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	253 873 12		1-6	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	253 876 12		1-6	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	253 877 12		1-6	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	253 880 12		1-6	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	253 881 12		1-6	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	253 884 12		1-6	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	253 885 12		1-6	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	253 888 12		1-6	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	253 889 12		1-6	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	253 892 12		1-6	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	253 893 12		1-6	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	253 896 12		1-6	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	253 897 12		1-6	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	20°	253 900 12		1-6	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	20°	253 901 12		1-6	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	20°	253 904 12		1-6	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	20°	253 905 12		1-6	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	20°	253 908 12		1-6	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	20°	253 909 12		1-6	
	SH/LH (+LF2) + SGL	alle		-	-	-	-	12 m	10°	257 160 12		1-5
		alle		-	-	-	-	12 m	15°	257 161 12		1-5
		alle		-	-	-	-	12 m	20°	257 162 12		1-5
	SSL/LSL (+LF2) + SGL	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	257 163 12		1-6
		160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	257 164 12		1-6
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	257 167 12		1-6
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	257 168 12		1-6
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	257 171 12		1-6
		160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	257 172 12		1-6
		180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	10°	257 175 12		1-6
		160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	10°	257 176 12		1-6
		180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	10°	257 179 12		1-6
		160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	10°	257 180 12		1-6
		180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	10°	257 183 12		1-6
		160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	10°	257 184 12		1-6
		180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	257 187 12		1-6
160 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	257 188 12		1-6	
180 t		60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	257 191 12		1-6	
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	257 192 12		1-6	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	257 195 12		1-6	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	257 196 12		1-6	
180 t		60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	257 199 12		1-6	
160 t		0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	257 200 12		1-6	
180 t		60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	257 203 12		1-6	
160 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	257 204 12		1-6	
180 t		60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	257 207 12		1-6	
160 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	257 208 12		1-6	
180 t		60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	257 211 12		1-6	
160 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	257 212 12		1-6	
180 t		60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	257 215 12		1-6	
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	257 216 12		1-6	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	257 219 12		1-6	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	257 220 12		1-6	
180 t		60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	20°	257 223 12		1-6	
160 t		0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	20°	257 224 12		1-6	
180 t		60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	20°	257 227 12		1-6	
160 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	20°	257 228 12		1-6	
180 t		60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	20°	257 231 12		1-6	
160 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	20°	257 232 12		1-6	
SH/LH + SGL_S7		beide	beide	-	-	-	-	-	-	252 981 12		1-6



Bemerkung	Konfiguration (RZ)		Gegengewicht		Superlift			HA- -Pos.	SP- Länge [m]	SP- Offset	Deutsch			
			GG [t]	ZB [t]	MR / GGR [m] / [m]	SL-GG [t]	SL-Typ				Tabellen- Nummer	Index	Seiten	
HSSL_S7	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	-	-	253 541 12	_1	1-8	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	-	-	253 542 12	_1	1-8	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	-	-	253 543 12		1-10	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	-	-	253 544 12		1-10	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	-	-	253 545 12		1-10	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	-	-	253 546 12		1-10	
	140 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	-	-	253 912 12	_1	1-8	
	120 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	-	-	253 913 12	_1	1-8	
	140 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	-	-	253 914 12		1-10	
	120 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	-	-	253 915 12		1-10	
	140 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	-	-	253 916 12		1-10	
	120 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	-	-	253 917 12		1-10	
	SSL/LSL + SGL_S7	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	-	-	252 983 12		1-11
		180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	-	-	252 984 12		1-11
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	-	-	252 985 12		1-11	
180 t		60 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	-	-	252 986 12		1-11	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	-	-	252 987 12		1-11	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	-	-	252 988 12		1-11	
* HSWSL_S7	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	85°	24 - 96	-	-	-	253 547 12	_1	1-100	
	180 t	60 t	11,5 / 11,0	0	Std.-SL	85°	24 - 96	-	-	-	253 548 12	_1	1-16	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	85°	24 - 96	-	-	-	253 549 12		1-114	
	180 t	60 t	13,5 / 13,0	0	Std.-SL	85°	24 - 96	-	-	-	253 550 12		1-18	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	85°	24 - 96	-	-	-	253 551 12		1-114	
	180 t	60 t	15,5 / 15,0	0	Std.-SL	85°	24 - 96	-	-	-	253 552 12		1-18	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	75°	24 - 96	-	-	-	253 553 12	_1	1-100	
	180 t	60 t	11,5 / 11,0	0	Std.-SL	75°	24 - 96	-	-	-	253 554 12	_1	1-14	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	75°	24 - 96	-	-	-	253 555 12		1-114	
	180 t	60 t	13,5 / 13,0	0	Std.-SL	75°	24 - 96	-	-	-	253 556 12		1-16	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	75°	24 - 96	-	-	-	253 557 12		1-114	
	180 t	60 t	15,5 / 15,0	0	Std.-SL	75°	24 - 96	-	-	-	253 558 12		1-16	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	65°	24 - 96	-	-	-	253 559 12	_1	1-100	
	180 t	60 t	11,5 / 11,0	0	Std.-SL	65°	24 - 66	-	-	-	253 560 12	_1	1-6	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	65°	24 - 96	-	-	-	253 561 12		1-114	
	180 t	60 t	13,5 / 13,0	0	Std.-SL	65°	24 - 66	-	-	-	253 562 12		1-7	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	65°	24 - 96	-	-	-	253 563 12		1-114	
	180 t	60 t	15,5 / 15,0	0	Std.-SL	65°	24 - 72	-	-	-	253 564 12		1-8	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	55°	24 - 96	-	-	-	253 565 12	_1	1-99	
	180 t	60 t	11,5 / 11,0	0	Std.-SL	55°	24 - 48	-	-	-	253 566 12	_1	1-3	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	55°	24 - 96	-	-	-	253 567 12		1-114	
	180 t	60 t	13,5 / 13,0	0	Std.-SL	55°	24 - 48	-	-	-	253 568 12		1-3	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	55°	24 - 96	-	-	-	253 569 12		1-114	
	180 t	60 t	15,5 / 15,0	0	Std.-SL	55°	24 - 48	-	-	-	253 570 12		1-3	
	SH/LH + LF2 + SGL_S7	beide	beide	-	-	-	-	12 m	10°	-	-	252 989 12		1-6
		beide	beide	-	-	-	-	12 m	15°	-	-	252 990 12		1-6
		beide	beide	-	-	-	-	12 m	20°	-	-	252 991 12		1-6
	HSSL + LF2_S7	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	-	-	253 942 12	_1	1-8
		160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	-	-	253 943 12	_1	1-8
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	-	-	253 946 12		1-10
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	-	-	253 947 12		1-10	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	-	-	253 950 12		1-10	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	-	-	253 951 12		1-10	
180 t		60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	-	-	253 954 12	_1	1-8	
160 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	-	-	253 955 12	_1	1-8	
180 t		60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	-	-	253 958 12		1-10	
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	-	-	253 959 12		1-10	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	-	-	253 962 12		1-10	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	-	-	253 963 12		1-10	
180 t		60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	-	-	253 966 12	_1	1-8	
160 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	-	-	253 967 12	_1	1-8	
180 t		60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	-	-	253 970 12		1-10	
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	-	-	253 971 12		1-10	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	-	-	253 974 12		1-10	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	-	-	253 975 12		1-10	

Datum: 22.05.2012

Date:
Date:



Bemerkung Konfiguration (RZ)	Gegengewicht		Superlift			HA- -Pos.	SP- Länge [m]	SP- Offset	Deutsch			
	GG [t]	ZB [t]	MR / GGR [m] / [m]	SL-GG [t]	SL-Typ				Tabellen- Nummer	Index	Seiten	
SSL/LSL + LF2 + SGL_S7	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	252 998 12		1-11	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	252 999 12		1-11	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	253 000 12		1-11	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	253 526 12		1-11	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	253 527 12		1-11	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	253 528 12		1-11	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	253 529 12		1-11	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	253 530 12		1-11	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	253 531 12		1-11	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	253 532 12		1-11	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	253 533 12		1-11	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	253 534 12		1-11	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	253 535 12		1-11	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	253 536 12		1-11	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	253 537 12		1-11	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	253 538 12		1-11	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	253 539 12		1-11	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	253 540 12		1-11	
	SH/LH (+LF2) + SGL_S7	beide	beide	-	-	-	-	12 m	10°	256 309 12		1-4
		beide	beide	-	-	-	-	12 m	15°	256 310 12		1-4
		beide	beide	-	-	-	-	12 m	20°	256 311 12		1-4
	HSSL (+LF2)_S7	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	502 337 12		1-8
		160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	502 338 12		1-8
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	502 341 12		1-10
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	502 342 12		1-10	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	502 345 12		1-10	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	502 346 12		1-10	
180 t		60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	502 349 12		1-8	
160 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	502 350 12		1-8	
180 t		60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	502 353 12		1-10	
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	502 354 12		1-10	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	502 357 12		1-10	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	502 358 12		1-10	
180 t		60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	502 361 12		1-8	
160 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	502 362 12		1-8	
180 t		60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	502 365 12		1-10	
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	502 366 12		1-10	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	502 369 12		1-10	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	502 370 12		1-10	
SSL/LSL (+LF2) + SGL_S7		180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	502 373 12		1-9
		160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	502 374 12		1-9
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	502 377 12		1-9
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	502 378 12		1-9
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	502 381 12		1-9
		160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	502 382 12		1-9
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	502 385 12		1-9	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	502 386 12		1-9	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	502 389 12		1-9	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	502 390 12		1-9	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	502 393 12		1-9	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	502 394 12		1-9	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	502 397 12		1-9	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	502 398 12		1-9	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	502 401 12		1-9	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	502 402 12		1-9	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	502 405 12		1-9	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	502 406 12		1-9	

Datum: 22.05.2012

Date:
Date:



Bemerkung	Konfiguration (RZ)	Gegengewicht		Superlift			HA- -Pos.	SP- Länge [m]	SP- Offset	Deutsch		
		GG [t]	ZB [t]	MR / GGR [m] / [m]	SL-GG [t]	SL-Typ				Tabellen- Nummer	Index	Seiten

Die Lastmomentbegrenzung (LMB) ist nur für den Auslieferungsumfang kalibriert!
Längen, die nicht zum Auslieferungsumfang gehören, machen eine
Überprüfung, gegebenenfalls eine Neukalibrierung, der LMB erforderlich.

* Freigabe erst nach Test


Freigabe durch:

Datum:

Ort:

Unterschrift:

Datum: 22.05.2012



Specification for duty charts

The crane CC 2800-1, serial no. 62387 is authorized for operating to the duty charts below:

Note	Configuration (RZ)	Counterweight		Superlift			MB- -Pos.	Jib- Length [m]	Jib- Offset	English		
		CW [t]	CB [t]	MR / CWR [m] / [m]	SL-CW [t]	SL-Type				Chart- Number	Index	Pages
	RG0	0	0 t	-	-	-	-	-	-	167 500 12		1
	SMAB1	0	0 t	-	-	-	-	-	-	167 496 12		1
	SMAB2	0	0 t	-	-	-	-	-	-	167 497 12		1
	SH	all	0 t	-	-	-	-	-	-	167 250 12		1-10
		all	60 t	-	-	-	-	-	-	167 251 12		1-4
	SH/LH	all	0 t	-	-	-	-	-	-	167 252 12	1	1-13
		all	60 t	-	-	-	-	-	-	167 253 12	1	1-4
* * *	SW	160 t	0 t	-	-	-	85°	24 - 84	-	167 254 12		1-14
* * *		180 t	60 t	-	-	-	85°	24 - 84	-	167 255 12		1-14
* * *		160 t	60 t	-	-	-	85°	24 - 84	-	167 256 12		1-14
* * *		160 t	0 t	-	-	-	75°	24 - 84	-	167 257 12		1-13
* * *		180 t	60 t	-	-	-	75°	24 - 84	-	167 258 12		1-14
* * *		160 t	60 t	-	-	-	75°	24 - 84	-	167 259 12		1-14
* * *		160 t	0 t	-	-	-	65°	24 - 78	-	167 260 12		1-8
* * *		180 t	60 t	-	-	-	65°	24 - 84	-	167 261 12		1-10
* * *		160 t	60 t	-	-	-	65°	24 - 84	-	167 262 12		1-10
	SSL	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	167 263 12		1-9
		180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	167 264 12		1-9
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	167 265 12		1-9
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	167 266 12		1-9
		160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	167 267 12		1-9
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	167 268 12		1-9
		160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	167 269 12		1-9
		180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	167 270 12		1-9
		160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	167 271 12		1-9
		180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	167 272 12		1-9
		160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	167 273 12		1-9
		180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	167 274 12		1-9
		140 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	253 591 12		1-9
		120 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	253 592 12		1-9
		140 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	253 593 12		1-9
		120 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	253 594 12		1-9
		140 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	253 595 12		1-9
		120 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	253 596 12		1-9
		140 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	253 597 12		1-9
		120 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	253 598 12		1-9
		140 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	253 599 12		1-9
		120 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	253 600 12		1-9
		140 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	253 601 12		1-9
		120 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	253 602 12		1-9
	SSL/LSL	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	167 275 12	1	1-18
		180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	167 276 12	1	1-18
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	167 277 12	1	1-18
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	167 278 12	1	1-18
		160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	167 279 12	1	1-18
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	167 280 12	1	1-18
		160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	167 281 12	1	1-18
		180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	167 282 12	1	1-18
		160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	167 283 12	1	1-18
		180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	167 284 12	1	1-18
		160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	167 285 12	1	1-18
		180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	167 286 12	1	1-18



Note	Configuration (RZ)	Counterweight		Superlift		MB- -Pos.	Jib- Length [m]	Jib- Offset	English			
		CW [t]	CB [t]	MR / CWR [m] / [m]	SL-CW [t]				SL-Type	Chart- Number	Index	Pages
	SSL/LSL	140 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	253 603 12	_1	1-18
		120 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	253 604 12	_1	1-18
		140 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	253 605 12	_1	1-18
		120 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	253 606 12	_1	1-18
		140 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	253 607 12	_1	1-18
		120 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	253 608 12	_1	1-18
		140 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	253 609 12	_1	1-18
		120 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	253 610 12	_1	1-18
		140 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	253 611 12	_1	1-18
		120 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	253 612 12	_1	1-18
		140 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	253 613 12	_1	1-18
		120 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	253 614 12	_1	1-18
	* SFSL	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	24 - 96	15°	167 287 12		1-114
	*	180 t	60 t	11,5 / 11,0	0	Std.-SL	-	24 - 96	15°	167 288 12		1-18
	*	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	24 - 96	15°	167 289 12		1-114
	*	180 t	60 t	13,5 / 13,0	0	Std.-SL	-	24 - 96	15°	167 290 12		1-18
	*	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	24 - 96	15°	167 291 12		1-114
	*	180 t	60 t	15,5 / 15,0	0	Std.-SL	-	24 - 96	15°	167 292 12		1-18
	*	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	24 - 96	15°	167 293 12		1-114
	*	180 t	60 t	15,0 / 15,0	0	Tele-SL	-	24 - 96	15°	167 294 12		1-18
	*	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	24 - 96	15°	167 295 12		1-114
	*	180 t	60 t	15,0 / 13,0	0	Tele-SL	-	24 - 96	15°	167 296 12		1-18
	*	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	24 - 96	15°	167 297 12		1-114
	*	180 t	60 t	15,0 / 17,0	0	Tele-SL	-	24 - 96	15°	167 298 12		1-18
	* SWSL	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	85°	24 - 96	-	167 307 12		1-114
	*	180 t	60 t	11,5 / 11,0	0	Std.-SL	85°	24 - 96	-	167 308 12		1-18
	*	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	85°	24 - 96	-	167 309 12		1-114
	*	180 t	60 t	13,5 / 13,0	0	Std.-SL	85°	24 - 96	-	167 310 12		1-18
	*	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	85°	24 - 96	-	167 311 12		1-114
	*	180 t	60 t	15,5 / 15,0	0	Std.-SL	85°	24 - 96	-	167 312 12		1-18
	*	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	85°	24 - 96	-	167 313 12		1-114
	*	180 t	60 t	15,0 / 15,0	0	Tele-SL	85°	24 - 96	-	167 314 12		1-18
	*	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	85°	24 - 96	-	167 315 12		1-114
	*	180 t	60 t	15,0 / 13,0	0	Tele-SL	85°	24 - 96	-	167 316 12		1-18
	*	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	85°	24 - 96	-	167 317 12		1-114
	*	180 t	60 t	15,0 / 17,0	0	Tele-SL	85°	24 - 96	-	167 318 12		1-18
	*	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	75°	24 - 96	-	167 319 12		1-114
	*	180 t	60 t	11,5 / 11,0	0	Std.-SL	75°	24 - 96	-	167 320 12		1-18
	*	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	75°	24 - 96	-	167 321 12		1-114
	*	180 t	60 t	13,5 / 13,0	0	Std.-SL	75°	24 - 96	-	167 322 12		1-18
	*	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	75°	24 - 96	-	167 323 12		1-114
	*	180 t	60 t	15,5 / 15,0	0	Std.-SL	75°	24 - 96	-	167 324 12		1-18
	*	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	75°	24 - 96	-	167 325 12		1-114
	*	180 t	60 t	15,0 / 15,0	0	Tele-SL	75°	24 - 96	-	167 326 12		1-18
	*	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	75°	24 - 96	-	167 327 12		1-114
	*	180 t	60 t	15,0 / 13,0	0	Tele-SL	75°	24 - 96	-	167 328 12		1-18
	*	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	75°	24 - 96	-	167 329 12		1-114
	*	180 t	60 t	15,0 / 17,0	0	Tele-SL	75°	24 - 96	-	167 330 12		1-18
	*	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	65°	24 - 96	-	167 331 12		1-114
	*	180 t	60 t	11,5 / 11,0	0	Std.-SL	65°	24 - 96	-	167 332 12		1-11
	*	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	65°	24 - 96	-	167 333 12		1-114
	*	180 t	60 t	13,5 / 13,0	0	Std.-SL	65°	24 - 96	-	167 334 12		1-11
	*	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	65°	24 - 96	-	167 335 12		1-114
	*	180 t	60 t	15,5 / 15,0	0	Std.-SL	65°	24 - 96	-	167 336 12		1-11
	*	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	65°	24 - 96	-	167 337 12		1-114
	*	180 t	60 t	15,0 / 15,0	0	Tele-SL	65°	24 - 96	-	167 338 12		1-11
	*	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	65°	24 - 96	-	167 339 12		1-114
	*	180 t	60 t	15,0 / 13,0	0	Tele-SL	65°	24 - 96	-	167 340 12		1-11
	*	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	65°	24 - 96	-	167 341 12		1-114
	*	180 t	60 t	15,0 / 17,0	0	Tele-SL	65°	24 - 96	-	167 342 12		1-11

Datum: 22.05.2012

Date:
Date:



Note	Configuration (RZ)		Counterweight		Superlift			MB- -Pos.	Jib- Length [m]	Jib- Offset	English		
			CW [t]	CB [t]	MR / CWR [m] / [m]	SL-CW [t]	SL-Type				Chart- Number	Index	Pages
* SWSL	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	55°	24 - 96	-	167 343 12	1-111			
	180 t	60 t	11,5 / 11,0	0	Std.-SL	55°	24 - 72	-	167 344 12	1-7			
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	55°	24 - 96	-	167 345 12	1-111			
	180 t	60 t	13,5 / 13,0	0	Std.-SL	55°	24 - 72	-	167 346 12	1-7			
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	55°	24 - 96	-	167 347 12	1-111			
	180 t	60 t	15,5 / 15,0	0	Std.-SL	55°	24 - 72	-	167 348 12	1-7			
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	55°	24 - 96	-	167 349 12	1-111			
	180 t	60 t	15,0 / 15,0	0	Tele-SL	55°	24 - 72	-	167 350 12	1-7			
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	55°	24 - 96	-	167 351 12	1-111			
	180 t	60 t	15,0 / 13,0	0	Tele-SL	55°	24 - 72	-	167 352 12	1-7			
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	55°	24 - 96	-	167 353 12	1-111			
	180 t	60 t	15,0 / 17,0	0	Tele-SL	55°	24 - 72	-	167 354 12	1-7			
	* LFVL	both		15,5 / 15,0	0-300	Std.-SL	-	12 m	17,5°	221 397 12	1-16		
		both		15,0 / 15,0	0-300	Tele-SL	-	12 m	17,5°	221 398 12	1-16		
both		15,0 / 13,0	0-300	Tele-SL	-	12 m	17,5°	221 399 12	1-16				
both		15,0 / 17,0	0-300	Tele-SL	-	12 m	17,5°	221 400 12	1-16				
* SFVL	both		15,5 / 15,0	0-300	Std.-SL	-	12 m	13°	167 299 12	1-16			
	both		15,0 / 15,0	0-300	Tele-SL	-	12 m	13°	167 300 12	1-16			
	both		15,0 / 13,0	0-300	Tele-SL	-	12 m	13°	167 301 12	1-16			
	both		15,0 / 17,0	0-300	Tele-SL	-	12 m	13°	167 302 12	1-16			
	both		15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	167 303 12	1-16			
	both		15,0 / 15,0	0-300	Tele-SL	-	12 m	20°	167 304 12	1-16			
	both		15,0 / 13,0	0-300	Tele-SL	-	12 m	20°	167 305 12	1-16			
	both		15,0 / 17,0	0-300	Tele-SL	-	12 m	20°	167 306 12	1-16			
SH+LF2	all		-	-	-	-	12 - 36	10°	253 663 12	1-30			
	all		-	-	-	-	12 m	15°	253 664 12	1-10			
	all		-	-	-	-	12 - 36	20°	253 665 12	1-30			
	all		-	-	-	-	24 - 36	30°	254 766 12	1-20			
SH/LH+LF2	all		-	-	-	-	12 - 36	10°	253 666 12	1-21			
	all		-	-	-	-	12 m	15°	253 667 12	1-7			
	all		-	-	-	-	12 - 36	20°	253 668 12	1-21			
	all		-	-	-	-	24 - 36	30°	254 767 12	1-14			
SSL+LF2	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	253 669 12	1-27			
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	253 670 12	1-27			
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	253 671 12	1-27			
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	253 672 12	1-27			
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	253 673 12	1-27			
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	253 674 12	1-27			
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	253 675 12	1-27			
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	253 676 12	1-27			
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	253 677 12	1-27			
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	253 678 12	1-27			
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	253 679 12	1-27			
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	253 680 12	1-27			
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	253 681 12	1-27			
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	253 682 12	1-27			
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	253 683 12	1-27			
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	253 684 12	1-27			
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	253 685 12	1-27			
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	253 686 12	1-27			
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	253 687 12	1-27			
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	253 688 12	1-27			
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	253 689 12	1-9			
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	253 690 12	1-9			
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	253 691 12	1-9			
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	253 692 12	1-9			
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	253 693 12	1-9			
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	253 694 12	1-9			
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	253 695 12	1-9			
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	253 696 12	1-9			
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	253 697 12	1-9			
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	253 698 12	1-9			
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	253 699 12	1-9			
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	253 700 12	1-9			
180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	253 701 12	1-9				
160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	253 702 12	1-9				

Datum: 22.05.2012

Date:
Date:



Note	Configuration (RZ)	Counterweight		Superlift			MB-Pos.	Jib-Length [m]	Jib-Offset	English		
		CW [t]	CB [t]	MR / CWR [m] / [m]	SL-CW [t]	SL-Type				Chart-Number	Index	Pages
SSL/LSL+LF2	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	24 - 36	30°	254 934 12	1-18		
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	24 - 36	30°	254 935 12	1-18		
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	24 - 36	30°	254 938 12	1-18		
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	24 - 36	30°	254 939 12	1-18		
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	24 - 36	30°	254 942 12	1-18		
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	24 - 36	30°	254 943 12	1-18		
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	24 - 36	30°	254 946 12	1-18		
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	24 - 36	30°	254 947 12	1-18		
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	24 - 36	30°	254 950 12	1-18		
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	24 - 36	30°	254 951 12	1-18		
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	24 - 36	30°	254 954 12	1-18		
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	24 - 36	30°	254 955 12	1-18		
	SH(+LF2)	all	-	-	-	-	-	12 - 36	10°	254 590 12	1-30	
		all	-	-	-	-	-	12 - 36	15°	254 591 12	1-10	
		all	-	-	-	-	-	12 - 36	20°	254 592 12	1-30	
SH/LH(+LF2)	all	-	-	-	-	-	12 - 36	10°	254 593 12	1-18		
	all	-	-	-	-	-	12 - 36	15°	254 594 12	1-6		
	all	-	-	-	-	-	12 - 36	20°	254 595 12	1-18		
SSL(+LF2)	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	254 596 12	1-27		
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	254 597 12	1-27		
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	254 600 12	1-27		
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	254 601 12	1-27		
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	254 604 12	1-27		
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	254 605 12	1-27		
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	254 608 12	1-27		
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	254 609 12	1-27		
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	254 612 12	1-27		
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	254 613 12	1-27		
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	254 616 12	1-27		
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	254 617 12	1-27		
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	254 620 12	1-9		
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	254 621 12	1-9		
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	254 624 12	1-9		
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	254 625 12	1-9		
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	254 628 12	1-9		
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	254 629 12	1-9		
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	254 632 12	1-9		
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	254 633 12	1-9		
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	254 636 12	1-9		
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	254 637 12	1-9		
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	254 640 12	1-9		
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	254 641 12	1-9		
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	254 644 12	1-27		
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	254 645 12	1-27		
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	254 648 12	1-27		
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	254 649 12	1-27		
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	254 652 12	1-27		
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	254 653 12	1-27		
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	254 656 12	1-27		
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	254 657 12	1-27		
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	254 660 12	1-27		
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	254 661 12	1-27		
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	254 664 12	1-27		
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	254 665 12	1-27		
	SSL/LSL(+LF2)	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	254 668 12	1-21	
		160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	10°	254 669 12	1-21	
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	254 672 12	1-21	
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	10°	254 673 12	1-21	
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	254 676 12	1-21	
		160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	10°	254 677 12	1-21	
		180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	254 680 12	1-21	
		160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	10°	254 681 12	1-21	
		180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	254 684 12	1-21	
		160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	10°	254 685 12	1-21	
		180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	254 688 12	1-21	
		160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	10°	254 689 12	1-21	

Datum: 22.05.2012

Date:
Date:



Note Configuration (RZ)	Counterweight		Superlift			MB- -Pos.	Jib- Length [m]	Jib- Offset	English			
	CW [t]	CB [t]	MR / CWR [m] / [m]	SL-CW [t]	SL-Type				Chart- Number	Index	Pages	
SSL/LSL(+LF2)	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	254 692 12		1-7	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	254 693 12		1-7	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	254 696 12		1-7	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	254 697 12		1-7	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	254 700 12		1-7	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	254 701 12		1-7	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	254 704 12		1-7	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	254 705 12		1-7	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	254 708 12		1-7	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	254 709 12		1-7	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	254 712 12		1-7	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	254 713 12		1-7	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	254 716 12		1-21	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 - 36	20°	254 717 12		1-21	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	254 720 12		1-21	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 - 36	20°	254 721 12		1-21	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	254 724 12		1-21	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 - 36	20°	254 725 12		1-21	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	254 728 12		1-21	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 - 36	20°	254 729 12		1-21	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	254 732 12		1-21	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 - 36	20°	254 733 12		1-21	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	254 736 12		1-21	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 - 36	20°	254 737 12		1-21	
	SH/LH + SGL	160	0 t	-	-	-	-	-	-	167 475 12		1-1
		both	60 t	-	-	-	-	-	-	167 476 12		1-2
	SSL/LSL + SGL	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	167 477 12		1-6
		180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	167 478 12		1-6
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	167 479 12		1-6
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	167 480 12		1-6
		160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	167 481 12		1-6
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	167 482 12		1-6
160 t		0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	167 483 12		1-6	
180 t		60 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	167 484 12		1-6	
160 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	167 485 12		1-6	
180 t		60 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	167 486 12		1-6	
160 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	167 487 12		1-6	
180 t		60 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	167 488 12		1-6	
140 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	253 813 12		1-6	
120 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	-	-	253 814 12		1-6	
140 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	253 815 12		1-6	
120 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	-	-	253 816 12		1-6	
140 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	253 817 12		1-6	
120 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	-	-	253 818 12		1-6	
140 t		0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	253 819 12		1-6	
120 t		0 t	15,0 / 15,0	0-300	Tele-SL	-	-	-	253 820 12		1-6	
140 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	253 821 12		1-6	
120 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	-	-	253 822 12		1-6	
140 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	253 823 12		1-6	
120 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	-	-	253 824 12		1-6	
SH/LH + LF2 + SGL		all		-	-	-	-	12 m	10°	253 837 12		1-7
		all		-	-	-	-	12 m	15°	253 838 12		1-7
		all		-	-	-	-	12 m	20°	253 839 12		1-7
SSL/LSL + LF2 + SGL		180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	253 840 12		1-6
		160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	253 841 12		1-6
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	253 844 12		1-6
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	253 845 12		1-6
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	253 848 12		1-6
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	253 849 12		1-6	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	10°	253 852 12		1-6	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	10°	253 853 12		1-6	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	10°	253 856 12		1-6	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	10°	253 857 12		1-6	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	10°	253 860 12		1-6	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	10°	253 861 12		1-6	



Note	Counterweight		Superlift			MB- -Pos.	Jib- Length [m]	Jib- Offset	English			
	Configuration (RZ)	CW [t]	CB [t]	MR / CWR [m] / [m]	SL-CW [t]				SL-Type	Chart- Number	Index	Pages
SSL/LSL + LF2 + SGL	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	253 864 12		1-6	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	253 865 12		1-6	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	253 868 12		1-6	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	253 869 12		1-6	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	253 872 12		1-6	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	253 873 12		1-6	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	253 876 12		1-6	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	253 877 12		1-6	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	253 880 12		1-6	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	253 881 12		1-6	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	253 884 12		1-6	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	253 885 12		1-6	
	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	253 888 12		1-6	
	160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	253 889 12		1-6	
	180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	253 892 12		1-6	
	160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	253 893 12		1-6	
	180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	253 896 12		1-6	
	160 t	0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	253 897 12		1-6	
	180 t	60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	20°	253 900 12		1-6	
	160 t	0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	20°	253 901 12		1-6	
	180 t	60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	20°	253 904 12		1-6	
	160 t	0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	20°	253 905 12		1-6	
	180 t	60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	20°	253 908 12		1-6	
	160 t	0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	20°	253 909 12		1-6	
	SH/LH (+LF2) + SGL	all		-	-	-	-	12 m	10°	257 160 12		1-5
		all		-	-	-	-	12 m	15°	257 161 12		1-5
		all		-	-	-	-	12 m	20°	257 162 12		1-5
	SSL/LSL (+LF2) + SGL	180 t	60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	257 163 12		1-6
		160 t	0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	10°	257 164 12		1-6
		180 t	60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	257 167 12		1-6
		160 t	0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	10°	257 168 12		1-6
		180 t	60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	257 171 12		1-6
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	10°	257 172 12		1-6	
180 t		60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	10°	257 175 12		1-6	
160 t		0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	10°	257 176 12		1-6	
180 t		60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	10°	257 179 12		1-6	
160 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	10°	257 180 12		1-6	
180 t		60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	10°	257 183 12		1-6	
160 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	10°	257 184 12		1-6	
180 t		60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	257 187 12		1-6	
160 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	15°	257 188 12		1-6	
180 t		60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	257 191 12		1-6	
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	15°	257 192 12		1-6	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	257 195 12		1-6	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	15°	257 196 12		1-6	
180 t		60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	257 199 12		1-6	
160 t		0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	15°	257 200 12		1-6	
180 t		60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	257 203 12		1-6	
160 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	15°	257 204 12		1-6	
180 t		60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	257 207 12		1-6	
160 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	15°	257 208 12		1-6	
180 t		60 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	257 211 12		1-6	
160 t		0 t	11,5 / 11,0	0-300	Std.-SL	-	12 m	20°	257 212 12		1-6	
180 t		60 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	257 215 12		1-6	
160 t		0 t	13,5 / 13,0	0-300	Std.-SL	-	12 m	20°	257 216 12		1-6	
180 t		60 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	257 219 12		1-6	
160 t		0 t	15,5 / 15,0	0-300	Std.-SL	-	12 m	20°	257 220 12		1-6	
180 t		60 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	20°	257 223 12		1-6	
160 t		0 t	15,0 / 15,0	0-300	Tele-SL	-	12 m	20°	257 224 12		1-6	
180 t		60 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	20°	257 227 12		1-6	
160 t		0 t	15,0 / 13,0	0-300	Tele-SL	-	12 m	20°	257 228 12		1-6	
180 t		60 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	20°	257 231 12		1-6	
160 t		0 t	15,0 / 17,0	0-300	Tele-SL	-	12 m	20°	257 232 12		1-6	
SH/LH + SGL_S7		both	both	-	-	-	-	-	-	252 981 12		1-6